



ALKA - KLEEN

DESCRIPTION

ALKA-KLEEN is specially compounded to provide effective, high power emulsion cleaning with pleasant odour. ALKA-KLEEN quickly removes heavy buildups of grease, oil, carbon, and stubborn caked-on soils with no harmful effect on the users.

Features & Benefits

- Ready for use.
- Can be used in spray, foam, brush or dip applications, and water rinsed.
- Extremely cost effective.
- High level of safety to the operator, equipment and marine life.
- Does not contain hazardous petroleum hydrocarbons
- Biodegradable nature allows easy disposal.

Application and Use

ALKA-KLEEN may be applied undiluted by brushing, wiping or spraying. Then hose off with fresh or sea water ALKA-KLEEN can be used as a cleaner for metals, parts and tools, painted and unpainted surfaces, decks, bulkheads, machinery, engines and wherever grease, oil and grimy soils are a problem. For use in cleaning tray or tank cleaning of parts, tools, etc., apply ALKA-KLEEN undiluted or with 5 to 150 parts of water. Soak parts until the soil is softened and rinse with water or wipe with a clean cloth.

Technical Specification

Appearance : Luminous Green

Boiling Point : 110°C

Specific Gravity : Approx. 1.05 Flash Point : Above 65°C Evaporation Rate : Less than 1.0

Solubility in Water: Complete

Precaution

Before using ALKA-KLEEN always read and follow precautions and directions for use as prescribed on container label.

CSG INDUSTRIES PTE LTD

No. 50, Tuas Avenue 11, #01-22, Tuas Lot Singapore 639107 **Email**: info@dbond.com.sg

Tel: (65) 6262 0800 (65) 6262 0822

Fax: (65) 6268 4500